



Your satisfaction is our pursuit!

# **TECHNICAL DATA SHEET-WAT**





## **DESCRIPTION**

It is made of two layers of high quality kraft paper, with vertical and horizontal yarns (glass fiber) embedded between two layers of paper and coated with vegetable starch glue. Stickiness occurs after dipping into water; It has the characteristics of high viscosity, strong tensile resistance, tight fitting, sealing without warping, anti-unpacking, printing and so on. (Use with wet water sealer).

## **APPLICATIONS**

Water Activated Reinforced Kraft Paper Tape becomes more and more popular in packaging application, with a double layers of kraft paper combined with Prismatic longitudinal glass fiber in the middle layer, coated with natural starch glue which with the benefits of high tensile, environmentally friendly and biodegradable.

### **PRODUCT FEATURES**

Material: **Kraft paper+glass fiber**Overall Grade/Function: **Economic** 

Adhesive: **Starch Characteristics**:

- Recycled with the carton, environmentally friendly
- Prismatic longitudinal glass fiber structure to ensure anti-theft

## **CORE SIZE**

3 in / 7.7cm 1.49in / 3.8cm

# **COLOR**



# WIDTH

48mm 70mm 72mm 144mm

## **LENGTH**

137m 500m 762m

Contact your ADHES sales representative for other available sizes

## **URFACE PREPARATION**

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

### **SPECIFICATIONS**

Total Thickness (No glass fiber)

Tensile Strength (TD)

Arrang ement of warplines

Service Temperature

Applicable Temperature

Service Life

Storage Suggestion

#### STANDARD

0.13mm ±0.02 (130µm±20)

≥188N/25mm

Separación 19 mm(1-1-1-1)

-10 ° C ~+ 60 ° C

+10° C ~ 40° C

l Year

23°C±2°C(73°F), 50%

of Relative Humidity



G18-72762Y



G18-70137Y

1-1-1-1 represents the longitudinal arrangement of the yarn (spacing 19mm)



www.adhestech.com

YOUTUBE: @AdhesUS

E-MAIL: SALES@ADHESTECH.COM

ADDRESS: 1815 S SAM RAYBURNFWY SHERMAN TX 75090